

# P-Series Thor Interchange


- Interlocking finger connection method with single or dual locking sleeves for maximum security.
- Convenient 'Push-Twist and Click' connection provides a positive locking condition while connected.
- Corrosion resistant steel construction and a variety of other materials available to provide additional corrosion resistance.
- Optional safety-lock clip protects against accidental disconnection while coupling is in operation.
- Highly versatile selection of end connections includes Female NPTF, Male NPTF, and Hose barb.



Performance Specifications	Operating Bar (PSI)	Coupled Burst Bar (PSI)	Flow ΔP=0.4Bar (6.9 Bar Inlet)	Locking Mechanism
1/2"	21 (300)	331 (4,800)	250 CFM	Latch Fingers
'P' Series Interchange	Thor	National	Dixon	---
1/2"	PHC	Series 'A'	Dual-Lock	---

P-Series


## P-Series Thor Interchange (Coupler)



(Female Thread)

Part Number	Body Size	Thread Size	Body Material	Weight (lb)	List Price	Pack Qty
4PF4	1/2"	1/2"-14 NPTF	steel	0.64	<b>\$35.78</b>	25
4PF6	1/2"	3/4"-14 NPTF	steel	0.55	<b>35.78</b>	25
4PF6-B	1/2"	3/4"-14 NPTF	brass	0.58	<b>75.59</b>	25
4PF6-S	1/2"	3/4"-14 NPTF	303 SS	0.57	<b>257.83</b>	25

## P-Series Thor Interchange (Flanged-Sleeve Coupler)



(Female Thread)

Part Number	Body Size	Thread Size	Body Material	Weight (lb)	List Price	Pack Qty
4PF4-FS	1/2"	1/2"-14 NPTF	steel	0.66	<b>\$39.43</b>	25
4PF6-FS	1/2"	3/4"-14 NPTF	steel	0.58	<b>39.43</b>	25

## P-Series Thor Interchange (Nipple)



(Female Thread)

Part Number	Body Size	Thread Size	Body Material	Weight (lb)	List Price	Pack Qty
P4F3	1/2"	3/8"-18 NPTF	steel	0.30	<b>\$21.43</b>	25
P4F4	1/2"	1/2"-14 NPTF	steel	0.47	<b>23.22</b>	25
P4F4-B	1/2"	1/2"-14 NPTF	brass	0.49	<b>59.26</b>	25
P4F6	1/2"	3/4"-14 NPTF	steel	0.37	<b>23.32</b>	25
P4F6-B	1/2"	3/4"-14 NPTF	brass	0.39	<b>57.77</b>	25
P4F6-S	1/2"	3/4"-14 NPTF	303 SS	0.37	<b>133.40</b>	25
P4F8	1/2"	1"-11 1/2 NPTF	steel	0.39	<b>25.39</b>	25
P4F8-B	1/2"	1"-11 1/2 NPTF	brass	0.44	<b>59.83</b>	25

## P-Series Thor Interchange (Coupler)



(Male Thread)

Part Number	Body Size	Thread Size	Body Material	Weight (lb)	List Price	Pack Qty
4PM3	1/2"	3/8"-18 NPTF	steel	0.48	<b>\$31.42</b>	25
4PM4	1/2"	1/2"-14 NPTF	steel	0.48	<b>31.25</b>	25
4PM6	1/2"	3/4"-14 NPTF	steel	0.51	<b>31.25</b>	25
4PM6-S	1/2"	3/4"-14 NPTF	303 SS	0.50	<b>269.43</b>	25

Safety cables should be used, as found on page 39. A positive safeguard for air hose connections will keep the operator safe and help to meet today's safety standards.



Attention Required!

**OSHA Regulation Standards - 29CFR, 926.302(b)(1):** Pneumatic tools shall be secured to the hose or whip by some positive means to prevent the tool from becoming accidentally disconnected.