

SS269 SOFTWALL MARINE EXHAUST HOSE

- Heavy duty softwall marine exhaust hose for use as a flexible connection to transfer wet exhaust on marine engines.
- Heat resistant tube handles high temperatures found in marine engine compartments.
- Durable heat, ozone, and abrasion resistant cover.

Tube: Extruded specially compounded Nitrile.
Reinforcement: Textile.
Cover: Specially compounded Nitrile.
Temperature: -40° to +200°F.

Meets U.S.C.G TYPE Standards for specification SAE J2006 R1



I.D.	O.D.	BEND RADIUS	WORKING PRESSURE PSI	WEIGHT LB/FT	VACUUM
1"	1-7/16"		200	.46	
1-1/8"	1-9/16"		200	.49	N/A
1-1/4"	1-13/16"		200	.69	N/A
1-5/16"	1-7/8"		200	.71	N/A
1-3/8"	1-15/16"		200	.75	N/A
1-1/2"	2-1/16"		200	.82	N/A
1-5/8"	2-3/16"		200	.87	N/A
1-3/4"	2-5/16"		200	.92	N/A
1-7/8"	2-7/16"		200	.97	N/A
2"	2-9/16"		200	1.07	N/A
2-1/8"	2-11/16"		200	1.12	N/A
2-1/4"	2-13/16"		200	1.17	N/A
2-3/8"	2-15/16"		200	1.25	N/A
2-1/2"	3-1/16"		200	1.32	N/A
2-5/8"	3-3/16"		200	1.37	N/A
2-3/4"	3-5/16"		200	1.42	N/A
2-7/8"	3-7/16"		200	1.52	N/A
3"	3-5/8"		200	1.46	N/A
3-1/2"	4-1/8"		200	1.70	N/A
4"	4-5/8"		200	1.93	N/A
4-1/2"	5-1/8"		200	2.21	N/A
5"	5-15/16"		200	3.80	N/A
5-9/16"	6-1/2"		200	4.14	N/A
6"	6-15/16"		200	4.51	N/A
6-5/8"	7-9/16"		200	5.01	N/A
7"	7-15/16"		200	5.24	N/A
8"	8-15/16"		150	5.83	N/A
8-5/8"	9-1/2"		150	5.95	N/A
10"	10-3/4"		150	6.77	N/A
10-3/4"	11-5/8"		100	7.55	N/A
12"	12-7/8"		100	8.38	N/A
12-3/4"	13-5/8"		100	8.88	N/A